Steel Dropdeck

2 or 3 Ramp Dropdeck Trailers



STANDARD DESIGN AND PERFORMANCE CHARACTERISTICS

- Gross Vehicle Weight Rating (GVWR) of 68,000 lbs.
- Main beams designed with camber and built in the Maurer facility
- Web 1/4" high grade 100,000 yield steel
- Flange 3/8'x5" high grade 100,000 yield steel
- Cross members of 4"x3.2# 80,000 yield jr. I-beam on 16" centers
- Side rails of 6"x8.2# structural C Channel
- Brake size of 16.5"x7"
- Kingpin setting of 24"
- Upper deck length of 11'
- Transition drop of 19.5" between decks
- 102" overall width

STANDARD **FEATURES**

- 22,500 lb Tandem axles w/ ABS brakes (single axle) and 10 bolt hub piloted rims
- 3-Leaf heavy duty spring suspension
- Spring assist for trailers with ramps
- Stake pockets and pipe spooling at 9" intervals
- Winch track
- Rub rail of 2'x3/8' flat steel
- Holland Series 51000 2 speed landing gear
- Flooring of 2"x8" kiln dried and pressure treated Southern Yellow Pine
- PPG polyurethane primer w/ PPG urotec paint (std. color - Black)
- Sealed wiring system w/ 7-way receptacle -Designed by Trucklite for Maurer
- D.O.T. approved conspicuity tape and rubber mounted lights
- Color coded brake lines
- Manifest holder
- Anti-sail mudflaps



www.vanderhaags.com



Steel Dropdeck

Options



Twin Ramps

Three Ramps



Optional Tail



Spread Axle



Spring Assist for Ramps

Sliding Winch



Closed tandem 10-1 spread available



Tool Box

AVAILABLE OPTIONS

(for additional charges)

- Air ride Holland Neway
- Scaleomatic
- ABS on second axle
- LED lights
- Aluminum Tool Box
- Third Ramp for Beaver Tail
- Sliding Winches
- Front Bulkhead
- Aluminum Rims



ACHOL

Vander Haag's, Inc