

DEMCO

Grain Trailers - Steel and Aluminum



Doing Our Best to Provide You the Best

www.demco-products.com • 1.800.543.3626



The Best Ground Clearance in the Industry
Demco offers hopper bottom grain trailers in either steel or aluminum configurations.

DEMCO

Steel Grain Trailers

Steel Grain Trailer Standard Features

- 3-leaf heavy duty SAF Holland spring suspensions
- 22.5K Arvin Meritor axles with Wabco ABS brakes (single axle) and 10 bolt hub piloted rims
- Holland Atlas 55 2-speed drop leg landing gear (24' 28' & 30' trailers)
- Holland Atlas 55 2-speed landing gear (34' – 42' trailers)
- Full center dividers on trailers 30' and up
- Rubber mounted LED lighting & sealed wiring system, 7 way receptacle by Trucklight
- Color coded brake lines
- Aluminum ladders (front & rear)
- Ladder rungs on inside of trailer
- Hopper sight windows
- Shur-Co manual roll tarp (Black, White, Red, Blue)
- Easy off tarp stops
- Roll tube deflectors
- Anti-sail Mudflaps
- D.O.T. approved conspicuity tape

Steel Grain Trailer Options

- | | |
|-------------------------------------|--|
| • Air Ride Suspension | • Electric Roll Tarp with Remote |
| • Manual Dump with Scale | • Hopper Work Lights |
| • ABS Installed on Second Axle | • 2-Speed Gear Reducer on Hopper Door |
| • Side Discharge Chute | • Aluminum Wheels |
| • Aluminum Platforms (front & rear) | • Stainless Steel Corners |
| • Pintle Hook | • Custom Trailer Color and Custom Tarp Color |
| • Front Mudflaps | • Tarp Cable Return (front & rear) |
| • Vented Hopper | • Tarp Saver Cords |
| • Double Ridge Strap | |
| • Electric Hopper Openers | |



Optional Aluminum Platform (front & rear)



Ladder Rungs on Inside of Trailer



Full Center Divider on Trailers 34' & up



Dump Valve with Scale



Tarp Cable Return (front & rear)

Aluminum Grain Trailers

Aluminum Grain Trailer Standard Features


- 3-leaf heavy duty SAF Holland spring suspensions for 28', 34', 36', 38', 40' & 42' trailers
- 22.5K Arvin Meritor tandem axles with Wabco ABS brakes (single axle) and 10 bolt hub piloted rims
- Standard air ride SAF Holland suspensions on 48' trailers.
- 25K Arvin Meritor tandem axles with Wabco ABS brakes (single axle) and 10 bolt hub piloted rims
- Holland Atlas 55 2 speed landing gear (34'-48' trailers)
- Holland Atlas 55 2 speed drop leg landing gear (on 28' trailers)
- Full center divider on all trailers 34' and up
- Rubber mounted LED lighting and sealed wiring system, 7 way receptacle by Truck-Lite
- Front & rear aluminum ladders
- Shur-Co manual roll tarp (Black, White, Red, or Blue)
- Easy off tarp stops
- Roll tube deflector
- Anti-sail mudflaps
- D.O.T. approved conspicuity tape

Aluminum Grain Trailer Options

- | | |
|--|---|
| • Painted Trailer | • Pintle Hook |
| • Deluxe Light Package | • ABS Installed on Second Axle |
| • 72", 74", 76" Wall Height | • Lift on 3rd Axle (available on 48' trailer) |
| • Air Ride Suspension | • Aluminum Wheels |
| • Manual Dump Valve with Scale | • Shur-Co Electric Roll Tarp with Remote |
| • Sight Windows | • Custom Tarp Color |
| • Aluminum Platforms (front & rear) | • Tarp Cable Return (front & rear) |
| • Front Mudflaps | • Tarp Saver Cords |
| • Vented Hopper | • Double Ridge Straps |
| • Electric Hopper Openers | • Side Chute |
| • Hopper Work Lights | |
| • 2-speed Gear Reducers on Hopper Door | |



Polished Aluminum Wheels



Side Chute for Swing Auger Applications



Double Ridge Strap



Vented Hopper



Pintle Hook (spring & air ride)



Maurer by Demco Steel Grain Trailer Specifications

	24'	28'	30'	34'	36'	38'	40'	42'
Height - ground to top rail	9'6"	9'6"	9'6"	9'6"	9'6"	9'6"	9'6"	9'6"
Number of hoppers	1	1	2	2	2	2	2	2
Hopper clearance empty (approx.)	25"	25"	25"	25"	25"	25"	25"	25"
New 22,500# axles	1	2	2	2	2	2	2	2
Cubic feet	810	855	1013	1152	1191	1255	1290	1324
Leveled bushels (approx.)	695	715	815	922	953	1010	1035	1060
Heaped bushels (approx.)	740	765	870	985	1020	1100	1120	1135
King pin to landing leg clearance	83"	87"	99"	80"	98"	107"	95"	90"
Kin pin setting	15"	15"	15"	18"	24"	15"	18"	24"
Hopper slope	35	35	35	35	35	35	35	35
Floor slope	28	28	28	35	35	35	31	35
Weight spring ride	6,600	9,000	9,800	10,200	10,400	10,700	11,000	11,200

(Information based on 66" wall height and 24.5 tires; air ride configurations add 240 lbs to the trailer)

Maurer by Demco Aluminum Grain Trailer Specifications

	28'	34'	36'	38'	40'	42'	50'
Height - ground to top rail	118"	118"	118"	118"	118"	118"	122"
Number of hoppers	1	2	2	2	2	2	2
Hopper clearance empty (approx.)	22"	22"	22"	22"	22"	22"	21"
Cubic feet	800	1148	1239	1310	1370	1472	1572
Leveled bushels (approx.)	643	923	996	1153	1101	1142	1263
Kin pin setting	16"	16"	16"	16"	16"	16"	16"
Hopper/floor slope	28-F/35-R	35	35	35	35	35	32
Weight air-ride	7,860	8,720	9,020	9,080	9,140	9,200	11,920
Weight spring ride	7,620	8,480	8,780	8,840	8,900	8,960	N/A

(Information based on 68" wall height and 24.5 tires)

The information contained herein is general in nature and is not intended for specific application purposes. Demco Manufacturing reserves the right to make changes in specifications or products at any time without notice or obligation. Trailers pictured in this brochure may feature optional equipment.



DEMCO

Doing Our Best to Provide You the Best

4010 320th Street • Boyden, Iowa 51234

1.800.543.3626

www.demco-products.com