

Platinum Series

2014 Model Types

Trailer Size	Trap Size	Ground Clearance	Slope Angle	Cu. Ft.	Bushels	Estimated Weight Alm. Sub/(8) Alm. wheels
34' x 96" x 68"	20" x 29"	24"	34 deg.	1115	900	8200 lbs.
34' x 96" x 74"	20" x 29"	24"	34 deg.	1230	990	8460 lbs.
40' x 96" x 68"	29" x 32"	24"	34 deg.	1350	1100	8760 lbs.
40' x 96" x 74"	29" x 32"	24"	34 deg.	1495	1200	8840 lbs.
42' x 96" x 68"	29" x 32"	24"	34 deg.	1400	1125	8960 lbs.
42' x 96" x 74"	29" x 32"	24"	34 deg.	1555	1250	9020 lbs.
42' x 102" x 74"	29" x 46"	18"	34 deg./38 deg. Slope/hopper	1800	1450	9400 lbs.
42' x 102" x 80"	29" x 46"	18"	38 deg.	1900	1550	9520 lbs.

- Steel sub frame adds approximately 125 lbs
- Steel wheels add approximately 190 lbs



Manual dump valve and pressure gauge with a weather tight box is standard with SAF Holland CBX-23 Fusion air-ride suspension.



Eight galvanized steel truss style tarp bows are standard along with two ridge straps.



Stoughton Trailers, Inc

416 S. Academy Street ■ Stoughton, Wisconsin 53589
608/873-2500 ■ FAX: 608/873-2575
www.stoughtontrailers.com