


The self-contained Post Driver is the choice for fencing contractors, landscapers, ranchers, farmers, and maintenance departments. Skid steer maneuverability allows the unit to be easily moved around buildings, storage sheds, trees and other obstacles, with minimal hydraulic power. Powered by a minimum of 10 GPM, the Post Driver can drive a 4" to 5" post into the ground in less than 15 seconds.



Drives railroad ties and guardrail posts.



All hydraulic-driven chain assembly.

FEATURES

- · Pile driving technology
- Manually adjusted variable speed to adjust strokes per minute
- · Up to 40 blows per minute
- · Drives posts straight and true on almost any terrain
- Easy and fast
- Powerful, simple design drives steel, wood, or even railroad ties
- · Rugged and reliable
- · 18° tilt each way



"A Legacy of Excellence Since 1948"

www.erskineattachments.com

SKID STEER

SPECIFICATIONS / OPTIONS

Model	Post Driver
M.S.R.P.	\$6,995
Part Number	900702
Operating Weight	1,000 lb.
Height	84"
Length	48.38"
Width	27"
Collars	8" x 9" (Railroad Ties)
	6" Round (Fence Posts)
	Steel (T Post)
Hydraulic Tilt Adjustment	18°
Maximum Post Size	8" × 9"
Minimum Post Size	"T" Post
Minimum Post Height Driven	8" Above Ground Level
Hammer Weight	330 lb.
Hammer Weight w/Ballast	530 lb.
Options	
Steel Shot Ballast- 200 lb.	\$265
Pistol Grip Control Harness	\$415
Loader Specific Wire Harness	\$140
Factory Installed Couplers	\$125

Fully enclosed for quiet operation

1,400 ft. lb. of **impact energy** (2,200 ft. lb. with ballast)



Optional:
Pistol Grip Control Harness
is required if skid steer is
NOT equipped with
attachment control system.
(Only needed when ordering
hydraulic angling model).



Wire harness for hydraulic models with attachment controls. Fits Cat/ASV (8-pin) and John Deere/New Holland/CASE/Bobcat (14-pin)



