



Rated Operating Capacity 931 lbs

Standard Equipment

Operator Station

ROPS
Suspension Seat w/ 2" seatbelt
Loader Control: Right-hand pilot hydraulic joystick controls
loader lift/tilt, with intermittent control of auxiliary hydraulics
Drive Control: Left-hand pilot hydraulic joystick controls
Hand Rotary Engine Speed Control
Multifunctional Display/Indicator: Fuel level, Engine Oil Pressure,
Hour Meter, Battery Voltage, Hydraulic Oil Temperature, Trip Meter
Tachometer, Engine Coolant Temperature, Multiple Languages
ROPS/FOPS
Meets ISO 3471: 2008
ISO 6683:2005
ISO 3449:2005 Level 1
Illumination: 2 fixed Forward Facing Lights 1 Rear Facing Light
Poly Roof Panel
Rear Window
Sound Insulation
Horn
Backup Alarm

Auxiliary Hydraulic System

Maximum System Pressure: 3000 psi
Pilot Hydraulic Joystick Control
Flat Faced Couplers: 5/8"
Auxiliary Pump Flow: 13.3 gpm
Manual Quick Attach
Attachment Control Kit
Variable Auxiliary Flow

Engine Specifications

Diesel 3-cylinder
Kubota D1803-CR-T
Displacement: 111.4 in³
Gross Horsepower: 37.5 hp
Torque Peak: 85.4 ft-lb
Engine-Driven Fan
Anti-Freeze Filled Radiator Cooling System
Dual Stage Intake Air Cleaner
Engine Block Heater

Emissions Controls: Meets All Emission Standards for Markets:

Service Capacity

Fuel Tank: 13 gal
Hydraulic Tank: 3.5 gal
Engine Coolant: 1.8 gal
Engine Oil (Including Filter): 7.4 quarts

Drive Train

Dual Hydraulic Drive Motors
Track Width: 11"
Length of Track on the Ground: 55"
2 Independent Torsion Axle Suspension
Ground Contact Area: 1210 in²
Roller Wheels: 12 high density polyurethane
Roller Wheel Diameter: 10"
Duo Cone Front & Rear

Electrical System

Upgradeable Wiring Harness
Normal Charge: 12V
Battery: 525 CCA
Alternator Charging System: 60 Amp
Port Outlet (Inside Operators Cab): 1 - 12V
Battery Disconnect

Operating Specifications

Radial Loader Arms
Operating Weight: 4175 lbs
Tipping Load: 2660 lbs
Operating Capacity: 931 lbs
Max. Travel Speed: 7.1 mph
Height to Bucket Pin: 101"
Maximum Dump Angle at Full Height: 43°
Rear Angle of Departure: 44°
Bucket Roll Back at Ground Level: 18.2°
Ground Clearance: Unloaded 10.8"
Overall Length with Bucket: 112"